



## HURON-30VA

### General Features

Length	6670 mm
Width	<b>1600 mm</b>
High	<b>2000 mm</b>
Ground clearance	320 mm
Axle distance	2700 mm
Maximum slope in running order	40%
Maximum inclination in running order	20%
Inner turning radius	2685 mm
External turning radius	5070 mm
Weight	6500 Kg

### Diesel engine

Brand	Caterpillar
Model	C 4.4 ACERT
Power	106 kW (140 CV)
Emissions	TIER 3

### Diesel engine

Brand	Caterpillar
Model	C3.6
Power	100 kW (134 CV)
Emissions	Stage V

### Transmission

Type	Powershift
Brand	JCB
Speeds	4
Drive	4 WD
Theoretical maximum speeds:	
1st Speed	4 Km/h
2st Speed	8 Km/h
3st Speed	14 Km/h
4st Speed	20 Km/h
Theoretical maximum reverse speeds:	
1st Speed	4 Km/h
2st Speed	8 Km/h
3st Speed	14 Km/h
4st Speed	20 Km/h

### Steering

Type	Hydro-assisted
Actuation	40° joint
Steering cylinders	2
Central Oscillation	- 10° +10°

### Brakes

Service (Oil bath)	Multidisc
Actuation	4 wheels
Parking (oil bath)	Negative
Actuation	Converter

### Tank Capacity

Diesel Tank	270 Lt
Hydraulic Tank	320 Lt
Water tank	100 Lt

### Cabin

Manufactured according to	ROPS / FOPS
Type	Closed
Air conditioning	Cold / Heat
Driving position	Fixed
Driver's seat	With belt
Rear camera	Yes
Access door	1

### Other

Tyres	14 R 17,5
Catalyst	Yes

### Performance

Concrete transport capacity	3 m <sup>3</sup>
Cover with tank locking cap	Yes

### Vat Drive

Type	Hydrostatics
Electrical regulation	0 a + 22 r.p.m
Cylinder capacity	64 cc

### Water pump Washing

Maximum pressure	100 bar
Flow rate	10,5 l/min

### OPTIONAL EQUIPMENT

#### Fire suppression

Dafo	Dust
Fogmaker	Water

#### Grease

Centralised	Automatic
-------------	-----------

Non-binding information document. Values are theoretical values. Specifications subject to change without notice.