



SCISSOR LIFT - FOX 45

General Features

Length	6085 mm
Width	1900 mm
High	2300 mm
Ground clearance	270 mm
Axle distance	2985 mm
Maximum slope in running order	30%
Maximum inclination in running order	28%
Inner turning radius	3000 mm
External turning radius	5350 mm
Weight	7000 kg
Maximum height	2700 mm
Maximum load	4500 kg
Platform rotation	± 90°

Diesel engine

Brand	Caterpillar
Model	C 4.4 ACERT
Power	106 kW (140 CV)
Emissions	TIER 3

Diesel engine

Brand	Caterpillar
Model	C3.6
Power	100 kW (134 CV)
Emissions	Stage V

Transmission

Type	Hydrostatics
Pump brand	PWG
Cylinder capacity	55 cc
Engine brand	Poclain
Type	Radial
Speeds	2 hydraulic
Drive	4 WD
Maximum speed	20 km/h

Steering

Type	Hydro-assisted
Actuation	40° joint
Steering cylinders	2
Central oscillation	10° + 10°

Brakes

Service (Oil bath)	Multidisc
Actuation	4 wheels
Parking	Negative
Actuation	4 wheels

Scissors

Load capacity	6000 kg
Maximum platform height	3680 mm
Scissor rotation	± 90°

Cabin

Manufactured according to	ROPS / FOPS
Type	Closed
Air conditioning	Cold - Heat
Driving position	Fixed
Driver's seat	With belt With suspension
Rear camera	Yes
Access doors	1

Capacities

Diesel Tank	190 lt
Hydraulic Tank	290 lt

Other

Tyres	14 - 17,5 (10 PR)
Catalyst	Yes

OPTIONAL EQUIPMENT

Fire suppression

Dafo	Dust
Fogmaker	Water

Grease

Centralised	Automatic
-------------	-----------

Non-binding information document. The values indicated are theoretical values. Specifications subject to change without notice.

SLF-2025I

