



HURON-25

General Features

Length	6800 mm
Width	1900 mm
High	2270 mm
Ground clearance	270 mm
Axle distance	3240 mm
Maximum slope in running order	30%
Maximum inclination in running order	28%
Inner turning radius	4430 mm
External turning radius	6850 mm
Weight	4950 Kg
Mixing capacity	2,5 m3
Vat capacity	3.750 Lt
Cover with tank locking cap	Hydraulic

Diesel engine

Brand	Caterpillar
Model	C 4.4 ACERT
Power	106 kW (140 CV)
Emissions	TIER 3

Diesel engine

Brand	Caterpillar
Model	C3.6
Power	100 kW (134 CV)
Emissions	Stage V

Transmission

Type	Hydrostatic
Pump brand	PWG
Cylinder capacity	55 cc
Engine brand	Poclair
Type	Radial
Speeds	2 hydraulic
Drive	4 WD
Maximum speed	20 km/h

Vat drive

Type	Hidrostatic
Electrical regulation	0 a + 22 r.p.m
Capacity	64 cc

Steering

Type	Hydro-assisted
Actuation	40° joint
Steering cylinders	2
Central oscillation	10° + 10°

Brakes

Service (Oil bath)	Multidisc
Actuation	4 wheels
Parking	Negative
Actuation	4 wheels

Cabin

Certification	ROPS / FOPS
Type	Closed
Air conditioning	Cold / Heat
Driving seat	Fixed
Driver's seat	With belt
Rear camera	Yes

Water pump Washing

Maximum pressure	100 bar
Flow rate	10,5 l/min

Capacities

Diesel tank	190 lt
Hydraulic Tank	290 lt

Other

Tyres	14 - 17,5 (10 PR)
Catalyst	Si

OPTIONAL EQUIPMENT

Fire suppression

Dafo	Dust
Fogmaker	Water

Grease

Centralised	Automatic
-------------	-----------

Non-binding information document. Values are theoretical values. Specifications subject to change without notice.