



HURON-50

General Features

Length	6880 mm
Width	2200 mm
High	2630 mm
Ground clearance	280 mm
Axle distance	4300 mm
Maximum slope in running order	30%
Maximum inclination in running order	28%
Inner turning radius	3400 mm
External turning radius	6750 mm
Weight	10800 Kg
Mixing capacity	5 m ³
Vat capacity	5100 Lt
Cover with tank locking cap	Yes

Diesel engine

Brand	Caterpillar
Model	C 7.1 ACERT
Power	129 kW (170 CV)
Emissions	TIER 3 A

Diesel engine

Brand	Caterpillar
Model	C4.4
Power	129 kW (170 CV)
Emissions	Stage V

Transmission

Type	Hydrostatic
Pump brand	Linde
Cylinder capacity	165 cc
Engine brand	Linde
Type	dual-axis
Speeds	2 hydraulic
Drive	4 WD
Maximum speed	20 km/h

Vat Drive

Type	Hydrostatic
Regulación eléctrica	0 a +22 r.p.m
Cylinder capacity	64 cc

Steering

Type	Hydro-assisted
Actuation	2 axes
	Front axle
Possibilities	Two axes
	Crab

Brakes

Service (Oil bath)	Multidisc
Drive	4 wheels
Parking	Negative
Drive	4 wheels

Cabin

Certification	ROPS / FOPS
Type	Closed
Air conditioning	Cold / Heat
Driving position	Fixed
Driver's seat	With belt
Rear camera	Yes

Water pump Washing

Maximum pressure	100 bar
Flow rate	10,5 l/min

Capacities

Diesel Tank	155 Lt
Hydraulic Tank	480 Lt

Other

Tyres	12,00 R 20
Catalyst	Yes

OPTIONAL EQUIPMENT

Fire suppression

Dafo	Dust
Fogmaker	Water

Grease

Centralised	Automatic
-------------	-----------

Non-binding information document. Values are theoretical values. Specifications subject to change without notice.