



PREMIER - 1A 




The smallest self-loading mixer in our range of production, **Premier 1A** has an actual output capacity of 1m³, accomplishing all safety and robustness of our equipment.

It is an articulated vehicle made on tubular structure and powered by Lombardini diesel engine, LDW 2204 with 47 CV at 3000 rpm, 4 cylinders, and water cooled.

Some of its main features are:


- Reducer for one gear forward and reverse
- 4-wheel drive
- 180° rotatory driving seat
- Hydro-assisted steering on central joint
- Automatically regulated hydrostatic transmission



Articulated unit with small dimensions, for working in the toughest conditions you could expect.

This type of self-loading concrete mixers is the answer to the demands of clients who long for agility and robustness in an unit simple and with easy maintenance. The optimal use of their features place them on top of our range.

PREMIER - 1A



SMALL DIMENSIONS, BIG FEATURES

The unit is made for working under the worst conditions with the best and most advanced features in technology and safety.



We can offer, as an optional, **Premier 1A** made for working at 5,200 MASL with no loss of power.

EASY TO TRANSPORT

In this global world, forwarding equipment in a fast and safe way has become a need an obligatory feature. **Premier 1A** has been designed for shipping three units in one only container, which can be delivered anywhere in the world.



Our “Premier” equipment is working in such different places as Angola, México, Dominican Republic, Russia, Brazil, Italy ... No need of more introductions; It is the answer to your requirements in civil Works with no doubt.

BRAND		C.O.C.
MODEL		PREMIER-1A
CONCRETE OUTPUT		1 m ³
DRUM CAPACITY		2,900 LIT
MOTOR	BRAND	LOMBARDINI
	MODEL	LDW 2204
	COOLING	WATER
	POWER	47 CV (33 KW)
TRANSMISSION	TYPE	HYDROSTATIC
	GEARS	2 (HYDRAULICS)
AXLES		MONOBLOCK WITH SLIDING DRIVE SHAFT
AXLES CAPACITY		2,500 Kgs.
DRIVE		4-WHEEL
CABIN		REAR, GIRATORY 180°
		SAFETY ARCH
STEERING		HYDRO-ASSISTED ON CENTRAL JOINT, 35° TO EACH SIDE
OPERATOR'S SEAT		ROTATORY 180°
BREAKS		DISC TYPE ON 4 WHEELS
DIMENSIONS		4,630 mm *1,660 mm*2,680 mm
DRUM		DOUBLE BLADE
DRUM MOVEMENT		HYDRAULIC IN BOTH DIRECTIONS
STEERING RADIOS	INNER	1,100 mm
	OUTTER	4,150 mm
POURING CHUTE		SWIVELLING AND ADJUSTABLE
CYCLE		7 - 10 MIN
SPEED	WORKING	0 TO 9.5 KM/H
	SHIFTING	20 KM/H ACCORDING TO SPANISH RULES
MAXIMUM SLOPE		30% (SAE)
ELECTRICAL SYSTEM		12 V BATTERY
POURING		REAR
POURING HEIGHT		900mm -1,000mm
TYRES		10.0/75-15
WEIGHT		2,650 KGS
HYDRAULIC OIL TANK		70 LIT
WATER TANK		200 LIT
FUEL TANK		45 LIT
SHOVEL CAPACITY		200 LIT

Due to the constant process of improvement at factory, all data are subject to modification without prior notice, being merely illustrative all data in this catalogue.

MADRID: Ctra de Valencia, Km 19,200. 28524 RIVAS VACIAMADRID (MADRID). FAX: +34916701005. e-mail:madrid@mlorenzana.com

LEÓN: Pol. Ind. Villacedré. 24009 VILLACEDRÉ (LEÓN). FAX: +34987849036. e-mail:leon@mlorenzana.com

www.mlorenzana.com +34 902 151 236

PREMIER - 1A



REF CAT: 00.AU.P1.13.EN.02

